

# bootwash

## double station

### Overview

The Double Bootwash Station allows two operators to clean boots simultaneously, making it suitable for medium-sized teams and busier site access points. Built with the same robust materials and user-friendly design as the Single Station, it enhances throughput while maintaining cleanliness and safety standards.




### Technical Specifications

Dimensions	
Length	510mm
Width	812mm
Height	1190mm
Weight	26kg
Users	2 operators at a time
Decking	38mm GRP deck
Outlet	Single 2" hosedtail outlet Black 800mm soft flexi-hose
Tray	Bitumen-coated steel tray with 25L capacity
Rail	Removable steel rail
Water Connection	15mm (1/2") hosedtail with non-return check valve


Water Supply Requirements	
UK standard tap pressure	~1 bar
Flow rate	approx. 15 litres per minute

Cleaning Tools
Manual operation – button-operated water hand brush supplied


Power Requirements
None




EASY  
MAINTENANCE



1/2" WATER  
CONNECTION



MOBILE



NO CIVILS

# bootwash

## double station



### Operational Notes

- All bootwash stations are manually operated
- Wash duration will vary depending on boot condition and material
- Quick installation on level, hardstanding surfaces (approx. 10 minutes)



### Optional Extras

- Fixed brush attachments (optional, not included as standard)
- Hand-wash taps
- Venturi chemical dosing system

### Maintenance

- Regularly check for blockages in the base by removing the GRP deck

