

# bootwash

## single station

### Overview

The Single Bootwash Station from Wheelwash Ltd is a compact and reliable boot cleaning solution designed for single-user operation. With a small footprint and durable build, this station is ideal for sites where space is limited but cleanliness and contamination control remain critical. Suitable for a wide range of industries, the Single Station helps reduce cleaning costs, supports site hygiene standards, and keeps walkways free of debris.



### Technical Specifications

Dimensions	
Length	510mm
Width	406mm
Height	1190mm
Weight	15kg
Users	1 operator at a time
Decking	38mm GRP deck
Outlet	Single 2" hosedtail outlet Black 800mm soft flexi-hose
Tray	Bitumen-coated steel tray with 12.8L capacity
Rail	Removable steel rail
Water Connection	15mm (1/2") hosedtail with non-return check valve

Water Supply Requirements	
UK standard tap pressure	~1 bar
Flow rate	approx. 15 litres per minute

Cleaning Tools
Manual operation – button-operated water hand brush supplied

Power Requirements
None

EASY  
MAINTENANCE

1/2" WATER  
CONNECTION

MOBILE

NO CIVILS

# bootwash

## single station

### Operational Notes

- All bootwash stations are manually operated
- Wash duration will vary depending on boot condition and material
- Designed for quick, efficient cleaning without requiring mains power
- Easy installation on level, hardstanding surfaces (approx. 10 minutes)



### Optional Extras

- Fixed brush attachment (optional, not included as standard)
- Hand-wash tap
- Venturi chemical dosing system

### Maintenance

- Regularly check for blockages in the base by removing the GRP deck

