

bootwash

triple station

Overview

The Triple Bootwash Station is the highest-capacity model in the range, allowing three users to clean simultaneously. Ideal for high-traffic environments and larger teams, this station maintains performance and durability while keeping installation and maintenance simple.



Technical Specifications

Dimensions	
Length	406mm
Width	1200mm
Height	1190mm
Weight	40kg
Users	3 operators at a time
Decking	38mm GRP deck
Outlet	Single 2" hosedtail outlet Black 800mm soft flexi-hose
Tray	Bitumen-coated steel tray with 38L capacity
Rail	Removable steel rail
Water Connection	15mm (1/2") hosedtail with non-return check valve

Water Supply Requirements	
UK standard tap pressure	~1 bar
Flow rate	approx. 15 litres per minute

Cleaning Tools
Manual operation – button-operated water hand brush supplied

Power Requirements
None



EASY
MAINTENANCE



1/2" WATER
CONNECTION



MOBILE



NO CIVILS

bootwash

triple station

Operational Notes

- All bootwash stations are manually operated
- Ideal for sites requiring fast throughput
- Wash time varies by contamination level
- Installation takes approximately 10 minutes on flat, hardstanding surfaces



Optional Extras

- Fixed brush attachments (optional, not included as standard)
- Hand-wash taps
- Venturi chemical dosing system

Maintenance

- GRP deck can be removed for easy blockage inspection and cleaning

